



Zhejiang Canglong Power Machinery Co., Ltd.

No.111, Yantang Rd, Changan Town, Haining City, Jiaxing City, Zhejiang, China
MOB/whatsapp +86 13675785567 EMAIL: graced@calonmarine.com
Grace DENG

Website: www.calonmarine.com FACEBOOK: https://www.facebook.com/428.gracedeng
Alibaba: https://calonmarine.en.alibaba.com/ Made-In-China: http://calonmarine.en.made-in-china.com/ Youtube: CG MARINE

QUOTATION (2025)

2 STROKE HS CODE: 8407210000

SPECIFICATION		IMAGE
MODEL	T3	
Type	2 Stroke	
Maximum output(kw)	2.2	
Dimension(mm)	S: 628*289*997	
Weight(kg)	S: 16.5	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	1	
Bore x Stroke(mm)	46.0 x 42.0	
Displacement(cc)	70	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start	
Ignition	CDI	
Fuel tank capacity(L)	1.4	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Propeller(in.)	7 1/4 x 6-B5	
Gear Shift	F-N	
Transom Height(mm)	441(S)	
Steering system	Tiller control	
SPECIFICATION		IMAGE
Model	T5	
Type	2 Stroke	
Maximum output(kw)	3.7	
Dimension(mm)	S: 677*322*1011 L: 677*322*1138	
Weight(kg)	S: 21.5 L: 22.5	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	1	
Bore x Stroke(mm)	54.0 x 45.0	
Displacement(cc)	103	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start	
Ignition	CDI	
Fuel tank capacity(L)	12	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Gear Shift	F-N-R	
Propeller(in.)	7 1/2*8-BL	
Transom Height(mm)	444(S) 571(L)	
Steering System	Tiller Control	
SPECIFICATION		IMAGE
Model	T9.8	 
Type	2 Stroke	
Maximum output(kw)	7.2	
Dimensions(mm)	S: 793*320*996 L: 793*320*1123	
Weight(kg)	S: 26 L: 27	
Maximum operating range(rpm)	5000-6000	
Number of cylinder	2	
Bore x Stroke(mm)	50.0 x 43.0	
Displacement(cc)	169	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start	
Ignition	CDI	
Fuel tank capacity(L)	12	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Gear Shift	F-N-R	
Propeller(in.)	8 3/4 * 8 1/2	
Transom Height(mm)	435(S) 562(L)	
Steering System	Tiller / Remote Control	
SPECIFICATION		IMAGE
Model	T15	 
Type	2 Stroke	
Maximum output(kw)	11	
Dimensions(mm)	S: 873 x 332 x 1043 L: 873 x 332 x 1170	
Weight(kg)	S: 38 L: 40	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	2	
Bore x Stroke(mm)	56.0 x 50.0	
Displacement(cc)	246	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start/ Electric Start	
Ignition	CDI	
Fuel tank capacity(L)	24	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Gear Shift	F-N-R	
Propeller(in.)	9 1/4*9-J	
Transom Height(mm)	440(S) 567(L)	
Steering System	Tiller / Remote Control	

SPECIFICATION		IMAGE
Model	T20	 
Type	2 Stroke	
Maximum output(kw)	14.7	
Dimension(mm)	S: 878*343*1077 L: 878*343*1204	
Weight(kg)	S: 41 L:42	
Maximum operating range(rpm)	5200-5800	
Number of cylinder	2	
Bore x Stroke(mm)	62.0 x 54.0	
Displacement(cc)	326	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start/ Electric Start	
Ignition	CDI	
Fuel tank capacity(L)	24	
Speed control	Twist grip type	
Gear ratio	1.85 (24:13)	
Gear Shift	F-N-R	
Propeller(in.)	9 1/4*9	
Transom Height(mm)	435(S) 562(L)	
Steering System	Tiller / Remote Control	
SPECIFICATION		IMAGE
Model	T30	
Type	2 Stroke	
Maximum output(kw)	22.1	
Dimension(mm)	S: 843*339*1146 L: 843*339*1273	
Weight(kg)	S: 53 L: 54.5	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	2	
Bore x Stroke(mm)	72.0 x 61.0	
Displacement(cc)	496	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start/ Electric Start	
Ignition	CDI	
Fuel tank capacity(L)	24	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Gear Shift	F-N-R	
Propeller(in.)	9 7/8 *12-F	
Transom Height(mm)	423(S) 550(L)	
Steering System	Tiller / Remote Control	
SPECIFICATION		IMAGE
Model	T40 ENDURO	
Type	2 Stroke	
Maximum output(kw)	29.4	
Dimension(mm)	S:1073*402*1237 L:1073*402*1364	
Weight(kg)	S:76 L:78	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	2	
Bore x Stroke(mm)	80.0 x 70.0	
Displacement(cc)	703	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start/ Electric Start	
Ignition	CDI	
Fuel tank capacity(L)	24	
Speed control	Twist grip type	
Gear ratio	26 : 13	
Gear Shift	F-N-R	
Propeller(in.)	11 1/8*13	
Transom Height(mm)	424(S) 550(L)	
Steering System	Tiller / Remote Control	
SPECIFICATION		IMAGE
Model	T15D (6B4)	
Type	2 Stroke	
Maximum output(kw)	11	
Dimensions(mm)	S:878*363*1062 L:878*363*1189	
Weight(kg)	S: 40 L:41.5	
Maximum operating range(rpm)	4500-5500	
Number of cylinder	2	
Bore x Stroke(mm)	56.0 x 50.0	
Displacement(cc)	246	
Engine lubrication system	Premixed Fuel	
Cooling system	Water/Thermostatic Control	
Starting system	Manual Start/ Electric Start	
Ignition	CDI	
Fuel tank capacity(L)	24	
Speed control	Twist grip type	
Gear ratio	2.08 (27:13)	
Gear Shift	F-N-R	
Propeller(in.)	9 1/4*9-J	
Transom Height(mm)	381(S) 508(L)	
Steering System	Tiller / Remote Control	

The machine display stand is not included.

4 STROKE HS CODE: 8407210000

SPECIFICATION		IMAGE	
MODEL	F6		
Type	4 Stroke		
Maximum output (kw)	4.4		
Dimension (mm)	S: 750*403*1040 L: 750*403*1167		
Weight (kg)	S: 27 L: 28		
Maximum operating range(rpm)	4500-5500		
Number of cylinder	1		
Bore x Stroke(mm)	62.0 x 46.0		
Displacement (cc)	139		
Engine lubrication system	Premixed Fuel		
Cooling system	Water/Thermostatic Control		
Starting system	Manual Start		
Ignition	CDI		
Fuel tank capacity(L)	12		
Speed control	Twist grip type		
Gear ratio	2.08 (27:13)		
Gear Shift	F-N-R		
Propeller(in.)	7 1/2x8-BL		
Transom Height(mm)	435(S) 562(L)		
Steering System	Tiller Control		
SPECIFICATION		IMAGE	
MODEL	F20		
Type	4 Stroke		
Maximum output (kw)	14.7		
Dimension (mm)	S: 1048*386*1097 L: 1048*386*1224		
Weight (kg)	S: 53.8 L: 55.8		
Maximum operating range(rpm)	5000-6000		
Number of cylinder	2		
Bore x Stroke(mm)	63.0 x 58.1		
Displacement (cc)	362		
Engine lubrication system	Premixed Fuel		
Cooling system	Water/Thermostatic Control		
Starting system	Manual Start/ Electric Start		
Ignition	CDI		
Fuel tank capacity(L)	24		
Speed control	Twist grip type		
Gear ratio	2.08 (27:13)		
Gear Shift	F-N-R		
Propeller(in.)	9 1/4x11-J1		
Transom Height(mm)	438 (S) 565(L)		
Steering System	Tiller / Remote Control		
SPECIFICATION		IMAGE	
MODEL	F60 EFI		
Type	4 Stroke SOHC		
Maximum output (kw)	44.1		
Dimension (mm)	L: 713*384*1435		
Weight (kg)	L: 113		
Maximum operating range(rpm)	5000-6000		
Number of cylinder	3		
Bore x Stroke(mm)	65.0 x 75.0		
Displacement (cc)	996		
Exhaust System	Center Exhaust		
Cooling system	Water/Thermostatic Control		
Starting system	Electric Start		
Ignition	ECM		
Fuel tank capacity(L)	24		
Steering System	Tiller / Remote Control		
Gear ratio	1.85 (24:13)		
Gear Shift	F-N-R		
Propeller(in.)	11 1/8x13-G		
Transom Height(mm)	527(L)		
WARRANTY: ONE YEAR OR 500 HOURS (WHICHEVER COMES FIRST).			
PAYMENT TERM: 100% T/T BEFORE SHIPMENT			
DELIVERY TIME: 3-7 DAYS FOR SAMPLE ORDER; 30-45 DAYS FOR BULK ORDER			
PACKAGE: CARTON BOX OUTSIDE WITH FOAM PROTECTION INSIDE			
LOOKING FORWARD TO COOPERATING WITH YOU!!!			